



ADVANTAGES

- Innovative pocket design for optimum air distribution and performance
- Higher number of pockets optimised for the lowest initial pressure drop and reduced energy consumption, even with shorter bags
- Fewer pockets provide an economical solution with less material waste
- Premium bag filter range with a robust metal header frame.
- Flexible dimensions and bag configurations to suit various applications

Application	Air conditioning applications
Frame	Galvanised steel
Media	Glass fiber
Dimensions	Filter front dimensions according EN 15805
Rec. final pressure drop acc. EN 13053	Initial pressure drop + 100 Pa or initial pressure drop x3 (whichever is lower)
Max airflow	1,25 x nominal flow
Max Temperature (°C)	70°C
Relative Humidity max	100%
Installation Options	Front and side access housings and frames are available.

Type	EN779	ISO 16890	Dimensions WxHxD (mm)	Airflow (m3/hr)	Pressure drop (Pa)	Bags	Media area (m²)	Weight (kg)	Energy (kWh/year)	Energy class	ePM1	ePM1min	ePM2,5	ePM2,5min	ePM10
1060 592x592x520-10	M5	ePM10 60%	592x592x520	3400	40	10	6,2	2,6	568	A	15	15	27	27	64
1060 592x490x520-10	M5	ePM10 60%	592x490x520	2800	40	10	5,1	2,4		A					
1060 490x592x520-8	M5	ePM10 60%	490x592x520	2800	40	8	5,1	2,3		A					
1060 592x287x520-10	M5	ePM10 60%	592x287x520	1700	40	10	3,1	1,5		A					
1060 287x592x520-5	M5	ePM10 60%	287x592x520	1700	40	5	3,1	1,6		A					
1060 287x287x520-5	M5	ePM10 60%	287x287x520	800	40	5	1,6	1,1		A					
1060 592x892x520-10	M5	ePM10 60%	592x892x520	5000	40	10	9,7	3,8		A					
1060 490x892x520-8	M5	ePM10 60%	490x892x520	4100	40	8	7,8	3,6		A					
1060 287x892x520-5	M5	ePM10 60%	287x892x520	2500	40	5	4,8	2,2		A					
1060 592x592x600-8	M5	ePM10 60%	592x592x600	3400	40	8	6	2,9	522	A	15	15	27	27	64
1060 592x490x600-8	M5	ePM10 60%	592x490x600	2800	40	8	4,5	2,4		A					
1060 490x592x600-6	M5	ePM10 60%	490x592x600	2800	40	6	4,5	2,4		A					
1060 592x287x600-8	M5	ePM10 60%	592x287x600	1700	40	8	3	1,5		A					
1060 287x592x600-4	M5	ePM10 60%	287x592x600	1700	40	4	3	1,5		A					
1060 287x287x600-4	M5	ePM10 60%	287x287x600	800	40	4	1,5	1,0		A					
1060 592x592x600-6	M5	ePM10 60%	592x592x600	3400	40	6	4,5	1,9	645	B	15	15	27	27	64
1060 592x490x600-6	M5	ePM10 60%	592x490x600	2800	40	6	3,6	1,6		B					

Type	EN779	ISO 16890	Dimensions WxHxD (mm)	Airflow (m3/hr)	Pressure drop (Pa)	Bags	Media area (m²)	Weight (kg)	Energy (kWh/year)	Energy class	ePM1	ePM1min	ePM2,5	ePM2,5min	ePM10
1060 490x592x600-5	M5	ePM10 60%	490x592x600	2800	40	5	3,6	1,6		B					
1060 592x287x600-6	M5	ePM10 60%	592x287x600	1700	40	6	2,3	1,1		B					
1060 287x592x600-3	M5	ePM10 60%	287x592x600	1700	40	3	2,3	1,1		B					
1060 287x287x600-3	M5	ePM10 60%	287x287x600	800	40	3	1,1	0,7		B					
1060 592x892x600-6	M5	ePM10 60%	592x892x600	5000	40	6	6,8	2,4		B					
1060 490x892x600-5	M5	ePM10 60%	490x892x600	4100	40	5	5,7	1,9		B					
1060 287x892x600-3	M5	ePM10 60%	287x892x600	2500	40	3	3,4	1,4		B					
1060 592x592x520-6	M5	ePM10 60%	592x592x520	3400	45	6	3,8	2	836	C	15	15	27	27	64
1060 592x490x520-6	M5	ePM10 60%	592x490x520	2800	45	6	3	1,8		C					
1060 490x592x520-5	M5	ePM10 60%	490x592x520	2800	45	5	3	1,8		C					
1060 592x287x520-6	M5	ePM10 60%	592x287x520	1700	45	6	1,8	1,2		C					
1060 287x592x520-3	M5	ePM10 60%	287x592x520	1700	45	3	1,9	1,2		C					
1060 287x287x520-3	M5	ePM10 60%	287x287x520	800	45	3	1,9	0,7		C					
1060 592x592x370-6	M5	ePM10 60%	592x592x370	3400	55	6	2,7	1,8	>1200	E	15	15	27	27	64
1060 592x490x370-6	M5	ePM10 60%	592x490x370	2800	55	6	2,2	1,6		E					
1060 490x592x370-5	M5	ePM10 60%	490x592x370	2800	55	5	2,2	1,6		E					
1060 592x287x370-6	M5	ePM10 60%	592x287x370	1700	55	6	1,3	1,2		E					
1060 287x592x370-3	M5	ePM10 60%	287x592x370	1700	55	3	1,3	1,2		E					
1060 287x287x370-3	M5	ePM10 60%	287x287x370	800	55	3	0,7	0,8		E					
2550 592x592x640-12	M6	ePM2,5 50%	592x592x640	3400	55	12	9,1	3,3	748	A	40	40	54	54	80
2550 592x490x640-12	M6	ePM2,5 50%	592x490x640	2800	55	12	7,6	3		A					
2550 490x592x640-10	M6	ePM2,5 50%	490x592x640	2800	55	10	7,6	3		A					
2550 592x287x640-12	M6	ePM2,5 50%	592x287x640	1700	55	12	4,6	2		A					
2550 287x592x640-6	M6	ePM2,5 50%	287x592x640	1700	55	6	4,6	2		A					
2550 287x287x640-6	M6	ePM2,5 50%	287x287x640	800	55	6	2,3	1,5		A					
2550 592x892x640-12	M6	ePM2,5 50%	592x892x640	5000	55	12	13,7	3,9		A					
2550 490x892x640-10	M6	ePM2,5 50%	490x892x640	4100	55	10	11,4	3,2		A					
2550 287x892x640-6	M6	ePM2,5 50%	287x892x640	2500	55	6	6,8	2,2		A					
2550 592x592x370-12	M6	ePM2,5 50%	592x592x370	3400	70	12	5,2	2,55	1280	C	40	40	54	54	80
2550 592x490x370-12	M6	ePM2,5 50%	592x490x370	2800	70	12	4,5	2,15		C					
2550 490x592x370-10	M6	ePM2,5 50%	490x592x370	2800	70	10	4,5	2,15		C					
2550 592x287x370-12	M6	ePM2,5 50%	592x287x370	1700	70	12	2,7	1,4		C					

Type	EN779	ISO 16890	Dimensions WxHxD (mm)	Airflow (m3/hr)	Pressure drop (Pa)	Bags	Media area (m²)	Weight (kg)	Energy (kWh/year)	Energy class	ePM1	ePM1min	ePM2,5	ePM2,5min	ePM10
2550 287x592x370-6	M6	ePM2,5 50%	287x592x370	1700	70	6	2,7	1,4		C					
2550 287x287x370-6	M6	ePM2,5 50%	287x287x370	800	70	6	1,3	0,8		C					
2550 592x892x370-12	M6	ePM2,5 50%	592x892x370	5000	70	12	8,1	2,9		C					
2550 490x892x370-10	M6	ePM2,5 50%	490x892x370	4100	70	10	6,8	2,6		C					
2550 287x892x370-6	M6	ePM2,5 50%	287x892x370	2500	70	6	4,0	1,4		C					
2550 592x592x520-10	M6	ePM2,5 50%	592x592x520	3400	65	10	6,2	2,9	992	C	40	40	54	54	80
2550 592x490x520-10	M6	ePM2,5 50%	592x490x520	2800	65	10	5,1	2,4		C					
2550 490x592x520-8	M6	ePM2,5 50%	490x592x520	2800	65	8	5,1	2,4		C					
2550 592x287x520-10	M6	ePM2,5 50%	592x287x520	1700	65	10	3,1	1,5		C					
2550 287x592x520-5	M6	ePM2,5 50%	287x592x520	1700	65	5	3,1	1,5		C					
2550 287x287x520-5	M6	ePM2,5 50%	287x287x520	800	65	5	1,6	1,1		C					
2550 592x892x520-10	M6	ePM2,5 50%	592x892x520	5000	65	10	9,7	4,4		C					
2550 490x892x520-8	M6	ePM2,5 50%	490x892x520	4100	65	8	7,8	4,0		C					
2550 287x892x520-5	M6	ePM2,5 50%	287x892x520	2500	65	5	4,8	2,6		C					
2550 592x592x600-8	M6	ePM2,5 50%	592x592x600	3400	60	8	6	2,9	872	B	40	40	54	54	80
2550 592x490x600-8	M6	ePM2,5 50%	592x490x600	2800	60	8	4,5	2,4		B					
2550 490x592x600-6	M6	ePM2,5 50%	490x592x600	2800	60	6	4,5	2,4		B					
2550 592x287x600-8	M6	ePM2,5 50%	592x287x600	1700	60	8	3	1,5		B					
2550 287x592x600-4	M6	ePM2,5 50%	287x592x600	1700	60	4	3	1,5		B					
2550 287x287x600-4	M6	ePM2,5 50%	287x287x600	800	55	4	1,5	1,0		B					
2550 592x592x520-8	M6	ePM2,5 50%	592x592x520	3400	65	8	5,2	2,6	997	C	40	40	54	54	80
2550 592x490x520-8	M6	ePM2,5 50%	592x490x520	2800	65	8	3,9	2,4		C					
2550 490x592x520-6	M6	ePM2,5 50%	490x592x520	2800	65	6	3,9	2,4		C					
2550 592x287x520-8	M6	ePM2,5 50%	592x287x520	1700	65	8	2,5	1,5		C					
2550 287x592x520-4	M6	ePM2,5 50%	287x592x520	1700	65	4	2,5	1,5		C					
2550 287x287x520-4	M6	ePM2,5 50%	287x287x520	800	65	4	1,3	0,8		C					
2550 592x592x370-8	M6	ePM2,5 50%	592x592x370	3400	80	8	3,6	2,4	1167	C	40	40	54	54	80
2550 592x490x370-8	M6	ePM2,5 50%	592x490x370	2800	80	8	2,7	2,1		C					
2550 490x592x370-6	M6	ePM2,5 50%	490x592x370	2800	80	6	2,7	2,1		C					
2550 592x287x370-8	M6	ePM2,5 50%	592x287x370	1700	80	8	1,8	1,5		C					
2550 287x592x370-4	M6	ePM2,5 50%	287x592x370	1700	80	4	1,8	1,5		C					
2550 287x287x370-4	M6	ePM2,5 50%	287x287x370	800	80	4	0,9	0,8		C					

Type	EN779	ISO 16890	Dimensions WxHxD (mm)	Airflow (m3/hr)	Pressure drop (Pa)	Bags	Media area (m²)	Weight (kg)	Energy (kWh/year)	Energy class	ePM1	ePM1min	ePM2,5	ePM2,5min	ePM10
2550 592x592x600-6	M6	ePM2,5 50%	592x592x600	3400	70	6	4,5	1,9	1189	C	40	40	54	54	80
2550 592x490x600-6	M6	ePM2,5 50%	592x490x600	2800	70	6	3,6	1,6		C					
2550 490x592x600-5	M6	ePM2,5 50%	490x592x600	2800	70	5	3,6	1,6		C					
2550 592x287x600-6	M6	ePM2,5 50%	592x287x600	1700	70	6	2,3	1,1		C					
2550 287x592x600-3	M6	ePM2,5 50%	287x592x600	1700	70	3	2,3	1,1		C					
2550 287x287x600-3	M6	ePM2,5 50%	287x287x600	800	70	3	1,1	0,7		C					
0160 592x592x640-12	F7	ePM1 60%	592x592x640	3400	65	12	9,1	3,3	803	A+	62	62	71	71	90
0160 592x490x640-12	F7	ePM1 60%	592x490x640	2800	65	12	7,6	3		A+					
0160 490x592x640-10	F7	ePM1 60%	490x592x640	2800	65	10	7,6	3		A+					
0160 592x287x640-12	F7	ePM1 60%	592x287x640	1700	65	12	4,6	2		A+					
0160 287x592x640-6	F7	ePM1 60%	287x592x640	1700	65	6	4,6	2		A+					
0160 287x287x640-6	F7	ePM1 60%	287x287x640	800	65	6	2,3	1,5		A+					
0160 592x892x640-12	F7	ePM1 60%	592x892x640	5000	65	12	13,7	3		A+					
0160 490x892x640-10	F7	ePM1 60%	490x892x640	4100	65	10	11,4	2,7		A+					
0160 287x892x640-6	F7	ePM1 60%	287x892x640	2500	65	6	6,8	1,8		A+					
0160 592x592x370-12	F7	ePM1 60%	592x592x370	3400	95	12	5,2	2,3	1275	C	62	62	71	71	90
0160 592x490x370-12	F7	ePM1 60%	592x490x370	2800	95	12	4,3	2,15		C					
0160 490x592x370-10	F7	ePM1 60%	490x592x370	2800	95	10	4,3	2,05		C					
0160 592x287x370-12	F7	ePM1 60%	592x287x370	1700	95	12	2,6	1,4		C					
0160 287x592x370-6	F7	ePM1 60%	287x592x370	1700	95	6	2,6	1,35		C					
0160 287x287x370-6	F7	ePM1 60%	287x287x370	800	95	6	1,3	0,8		C					
0160 592x892x370-12	F7	ePM1 60%	592x892x370	5000	95	12	8,1	2,5		C					
0160 490x892x370-10	F7	ePM1 60%	490x892x370	4100	95	10	6,8	2,2		C					
0160 287x892x370-6	F7	ePM1 60%	287x892x370	2500	95	6	4	1,5		C					
0160 592x592x520-10	F7	ePM1 60%	592x592x520	3400	75	10	6,2	2,6	943	A	62	62	71	71	90
0160 592x490x520-10	F7	ePM1 60%	592x490x520	2800	75	10	5,1	2,4		A					
0160 490x592x520-8	F7	ePM1 60%	490x592x520	2800	75	8	5,1	2,3		A					
0160 592x287x520-10	F7	ePM1 60%	592x287x520	1700	75	10	3,1	1,5		A					
0160 287x592x520-5	F7	ePM1 60%	287x592x520	1700	75	5	3,1	1,6		A					
0160 287x287x520-5	F7	ePM1 60%	287x287x520	800	75	5	1,6	1,1		A					
0160 592x892x520-10	F7	ePM1 60%	592x892x520	5000	75	10	9,7	3,8		A					
0160 490x892x520-8	F7	ePM1 60%	490x892x520	4100	75	8	7,8	3,6		A					

Type	EN779	ISO 16890	Dimensions WxHxD (mm)	Airflow (m3/hr)	Pressure drop (Pa)	Bags	Media area (m²)	Weight (kg)	Energy (kWh/year)	Energy class	ePM1	ePM1min	ePM2,5	ePM2,5min	ePM10
0160 287x892x520-5	F7	ePM1 60%	287x892x520	2500	75	5	4,8	2,2		A					
0160 592x592x600-8	F7	ePM1 60%	592x592x600	3400	75	8	6	2,9	946	A	62	62	71	71	90
0160 592x490x600-8	F7	ePM1 60%	592x490x600	2800	75	8	4,5	2,4		A					
0160 490x592x600-6	F7	ePM1 60%	490x592x600	2800	75	6	4,5	2,4		A					
0160 592x287x600-8	F7	ePM1 60%	592x287x600	1700	75	8	3	1,5		A					
0160 287x592x600-4	F7	ePM1 60%	287x592x600	1700	75	4	3	1,5		A					
0160 287x287x600-4	F7	ePM1 60%	287x287x600	800	75	4	1,5	1,0		A					
0160 592x592x520-8	F7	ePM1 60%	592x592x520	3400	85	8	5,2	2,6	1093	B	62	62	71	71	90
0160 592x490x520-8	F7	ePM1 60%	592x490x520	2800	85	8	3,9	2,4		B					
0160 490x592x520-6	F7	ePM1 60%	490x592x520	2800	85	6	3,9	2,4		B					
0160 592x287x520-8	F7	ePM1 60%	592x287x520	1700	85	8	2,5	1,5		B					
0160 287x592x520-4	F7	ePM1 60%	287x592x520	1700	85	4	2,5	1,5		B					
0160 287x287x520-4	F7	ePM1 60%	287x287x520	800	85	4	1,3	0,8		B					
0160 592x592x370-8	F7	ePM1 60%	592x592x370	3400	115	8	3,6	2,4	1670	D	62	62	71	71	90
0160 592x490x370-8	F7	ePM1 60%	592x490x370	2800	115	8	2,7	2,1		D					
0160 490x592x370-6	F7	ePM1 60%	490x592x370	2800	115	6	2,7	2,1		D					
0160 592x287x370-8	F7	ePM1 60%	592x287x370	1700	115	8	1,8	1,5		D					
0160 287x592x370-4	F7	ePM1 60%	287x592x370	1700	115	4	1,8	1,5		D					
0160 287x287x370-4	F7	ePM1 60%	287x287x370	800	115	4	0,9	0,8		D					
0160 592x592x600-6	F7	ePM1 60%	592x592x600	3400	85	6	4,5	1,9	1217	C	62	62	71	71	90
0160 592x490x600-6	F7	ePM1 60%	592x490x600	2800	85	6	3,6	1,6		C					
0160 490x592x600-5	F7	ePM1 60%	490x592x600	2800	85	5	3,6	1,6		C					
0160 592x287x600-6	F7	ePM1 60%	592x287x600	1700	85	6	2,3	1,1		C					
0160 287x592x600-3	F7	ePM1 60%	287x592x600	1700	85	3	2,3	1,1		C					
0160 287x287x600-3	F7	ePM1 60%	287x287x600	800	85	3	1,1	0,7		C					
0170 592x592x640-12	F7	ePM1 70%	592x592x640	3400	80	12	9,1	3,3	967	A	70	70	79	79	93
0170 592x490x640-12	F7	ePM1 70%	592x490x640	2800	80	12	7,6	3		A					
0170 490x592x640-10	F7	ePM1 70%	490x592x640	2800	80	10	7,6	3		A					
0170 592x287x640-12	F7	ePM1 70%	592x287x640	1700	80	12	4,6	2		A					
0170 287x592x640-6	F7	ePM1 70%	287x592x640	1700	80	6	4,6	2		A					
0170 287x287x640-6	F7	ePM1 70%	287x287x640	800	80	6	2,3	1,5		A					
0170 592x892x640-12	F7	ePM1 70%	592x892x640	5000	80	12	13,7	3		A					

Type	EN779	ISO 16890	Dimensions WxHxD (mm)	Airflow (m3/hr)	Pressure drop (Pa)	Bags	Media area (m²)	Weight (kg)	Energy (kWh/year)	Energy class	ePM1	ePM1min	ePM2,5	ePM2,5min	ePM10
0170 490x592x600-6	F7	ePM1 70%	490x592x600	2800	100	6	4,5	2,4		B					
0170 490x892x640-10	F7	ePM1 70%	490x892x640	4100	80	10	11,4	2,7		A					
0170 287x892x640-6	F7	ePM1 70%	287x892x640	2500	80	6	6,8	1,8		A					
0170 592x592x370-12	F7	ePM1 70%	592x592x370	3400	130	12	5,2	2,3	1677	D	70	70	79	79	93
0170 592x490x370-12	F7	ePM1 70%	592x490x370	2800	130	12	4,3	2,15		D					
0170 490x592x370-10	F7	ePM1 70%	490x592x370	2800	130	10	4,3	2,05		D					
0170 592x287x370-12	F7	ePM1 70%	592x287x370	1700	130	12	2,6	1,4		D					
0170 287x592x370-6	F7	ePM1 70%	287x592x370	1700	130	6	2,6	1,35		D					
0170 287x287x370-6	F7	ePM1 70%	287x287x370	800	130	6	1,3	0,8		D					
0170 592x892x370-12	F7	ePM1 70%	592x892x370	5000	130	12	8,1	2,5		D					
0170 490x892x370-10	F7	ePM1 70%	490x892x370	4100	130	10	6,8	2,2		D					
0170 287x892x370-6	F7	ePM1 70%	287x892x370	2500	130	6	4	1,5		D					
0170 592x592x520-10	F7	ePM1 70%	592x592x520	3400	100	10	6,2	2,6	1196	B	70	70	79	79	93
0170 592x490x520-10	F7	ePM1 70%	592x490x520	2800	100	10	5,1	2,4		B					
0170 490x592x520-8	F7	ePM1 70%	490x592x520	2800	100	8	5,1	2,3		B					
0170 592x287x520-10	F7	ePM1 70%	592x287x520	1700	100	10	3,1	1,5		B					
0170 287x592x520-5	F7	ePM1 70%	287x592x520	1700	100	5	3,1	1,6		B					
0170 287x287x520-5	F7	ePM1 70%	287x287x520	800	100	5	1,6	1,1		B					
0170 592x892x520-10	F7	ePM1 70%	592x892x520	5000	100	10	9,7	3,8		B					
0170 490x892x520-8	F7	ePM1 70%	490x892x520	4100	100	8	7,8	3,6		B					
0170 287x892x520-5	F7	ePM1 70%	287x892x520	2500	100	5	4,8	2,2		B					
0170 592x592x600-8	F7	ePM1 70%	592x592x600	3400	100	8	6	2,9	1221	B	70	70	79	79	93
0170 592x490x600-8	F7	ePM1 70%	592x490x600	2800	100	8	4,5	2,4		B					
0170 592x287x600-8	F7	ePM1 70%	592x287x600	1700	100	8	3	1,5		B					
0170 287x592x600-4	F7	ePM1 70%	287x592x600	1700	100	4	3	1,5		B					
0170 287x287x600-4	F7	ePM1 70%	287x287x600	800	100	4	1,5	1,0		B					
0170 592x592x520-8	F7	ePM1 70%	592x592x520	3400	110	8	5,2	2,6	1382	C	70	70	79	79	93
0170 592x490x520-8	F7	ePM1 70%	592x490x520	2800	110	8	3,9	2,4		C					
0170 490x592x520-6	F7	ePM1 70%	490x592x520	2800	110	6	3,9	2,4		C					
0170 592x287x520-8	F7	ePM1 70%	592x287x520	1700	110	8	2,5	1,5		C					
0170 287x592x520-4	F7	ePM1 70%	287x592x520	1700	110	4	2,5	1,5		C					
0170 287x287x520-4	F7	ePM1 70%	287x287x520	800	110	4	1,3	0,8		C					

Type	EN779	ISO 16890	Dimensions WxHxD (mm)	Airflow (m3/hr)	Pressure drop (Pa)	Bags	Media area (m²)	Weight (kg)	Energy (kWh/year)	Energy class	ePM1	ePM1min	ePM2,5	ePM2,5min	ePM10
0170 592x592x370-8	F7	ePM1 70%	592x592x370	3400	155	8	3,6	2,4	2116	D	70	70	79	79	93
0170 592x490x370-8	F7	ePM1 70%	592x490x370	2800	155	8	2,7	2,1		D					
0170 490x592x370-6	F7	ePM1 70%	490x592x370	2800	155	6	2,7	2,1		D					
0170 592x287x370-8	F7	ePM1 70%	592x287x370	1700	155	8	1,8	1,5		D					
0170 287x592x370-4	F7	ePM1 70%	287x592x370	1700	155	4	1,8	1,5		D					
0170 287x287x370-4	F7	ePM1 70%	287x287x370	800	155	4	0,9	0,8		D					
0170 592x592x600-6	F7	ePM1 70%	592x592x600	3400	115	6	4,5	1,9	1584	D	70	70	79	79	93
0170 592x490x600-6	F7	ePM1 70%	592x490x600	2800	115	6	3,6	1,6		D					
0170 490x592x600-5	F7	ePM1 70%	490x592x600	2800	115	5	3,6	1,6		D					
0170 592x287x600-6	F7	ePM1 70%	592x287x600	1700	115	6	2,3	1,1		D					
0170 287x592x600-3	F7	ePM1 70%	287x592x600	1700	115	3	2,3	1,1		D					
0170 287x287x600-3	F7	ePM1 70%	287x287x600	800	115	3	1,1	0,7		D					
0185 592x592x640-12	F9	ePM1 85%	592x592x640	3400	125	12	9,1	3,3	1520	C	87	87	91	91	98
0185 592x490x640-12	F9	ePM1 85%	592x490x640	2800	125	12	6,8	3		C					
0185 490x592x640-10	F9	ePM1 85%	490x592x640	2800	125	10	7,6	3		C					
0185 592x287x640-12	F9	ePM1 85%	592x287x640	1700	125	12	4,9	2		C					
0185 287x592x640-6	F9	ePM1 85%	287x592x640	1700	125	6	4,6	2		C					
0185 287x287x640-6	F9	ePM1 85%	287x287x640	800	125	6	2,1	1,5		C					
0185 592x892x640-12	F9	ePM1 85%	592x892x640	5000	125	12	13,7	3		C					
0185 490x892x640-10	F9	ePM1 85%	490x892x640	4100	125	10	11,4	2,7		C					
0185 287x892x640-6	F9	ePM1 85%	287x892x640	2500	125	6	6,8	1,8		C					
0185 592x592x370-12	F9	ePM1 85%	592x592x370	3400	225	12	5,2	2,25	>2400	E	87	87	91	91	98
0185 592x490x370-12	F9	ePM1 85%	592x490x370	2800	225	12	4,5	2,15		E					
0185 490x592x370-10	F9	ePM1 85%	490x592x370	2800	225	10	4,4	2		E					
0185 592x287x370-12	F9	ePM1 85%	592x287x370	1700	225	12	2,7	1,4		E					
0185 287x592x370-6	F9	ePM1 85%	287x592x370	1700	225	6	2,7	1,35		E					
0185 287x287x370-6	F9	ePM1 85%	287x287x370	800	225	6	1,3	0,8		E					
0185 592x892x370-12	F9	ePM1 85%	592x892x370	5000	225	12	8,1	2,5		E					
0185 490x892x370-10	F9	ePM1 85%	490x892x370	4100	225	10	6,8	2,2		E					
0185 287x892x370-6	F9	ePM1 85%	287x892x370	2500	225	6	4	1,5		E					
0185 592x592x520-10	F9	ePM1 85%	592x592x520	3400	155	10	6,2	2,5	1880	D	87	87	91	91	98
0185 592x490x520-10	F9	ePM1 85%	592x490x520	2800	155	10	5,1	2,4		D					

Type	EN779	ISO 16890	Dimensions WxHxD (mm)	Airflow (m3/hr)	Pressure drop (Pa)	Bags	Media area (m²)	Weight (kg)	Energy (kWh/year)	Energy class	ePM1	ePM1min	ePM2,5	ePM2,5min	ePM10
0185 490x592x520-8	F9	ePM1 85%	490x592x520	2800	155	8	5,1	2,4		D					
0185 592x287x520-10	F9	ePM1 85%	592x287x520	1700	155	10	3,5	1,5		D					
0185 287x592x520-5	F9	ePM1 85%	287x592x520	1700	155	5	3,1	1,5		D					
0185 287x287x520-5	F9	ePM1 85%	287x287x520	800	155	5	1,6	1,1		D					
0185 592x892x520-10	F9	ePM1 85%	592x892x520	5000	155	10	9,7	4,1		D					
0185 490x892x520-8	F9	ePM1 85%	490x892x520	4100	155	8	7,8	3,6		D					
0185 287x892x520-5	F9	ePM1 85%	287x892x520	2500	155	5	4,8	2,5		D					
0185 592x592x600-8	F9	ePM1 85%	592x592x600	3400	160	8	6	2,9	1956	D	87	87	91	91	98
0185 592x490x600-8	F9	ePM1 85%	592x490x600	2800	160	8	4,6	2,4		D					
0185 490x592x600-6	F9	ePM1 85%	490x592x600	2800	160	6	4,5	2,4		D					
0185 592x287x600-8	F9	ePM1 85%	592x287x600	1700	160	8	3	1,5		D					
0185 287x592x600-4	F9	ePM1 85%	287x592x600	1700	160	4	3	1,5		D					
0185 287x287x600-4	F9	ePM1 85%	287x287x600	800	160	4	1,5	1,0		D					
0185 592x592x520-8	F9	ePM1 85%	592x592x520	3400	175	8	5,2	2,6	2266	D	87	87	91	91	98
0185 592x490x520-8	F9	ePM1 85%	592x490x520	2800	175	8	3,9	2,4		D					
0185 490x592x520-6	F9	ePM1 85%	490x592x520	2800	175	6	3,9	2,4		D					
0185 592x287x520-8	F9	ePM1 85%	592x287x520	1700	175	8	2,5	2,4		D					
0185 287x592x520-4	F9	ePM1 85%	287x592x520	1700	175	4	2,5	1,5		D					
0185 287x287x520-4	F9	ePM1 85%	287x287x520	800	175	4	0,9	0,8		D					

Energy Consumption, kWh/year: Calculated according to Eurovent Guideline 4/21-2019

Energy class: according to Eurovent RS 4/C/001-2019

EPD (Environmental Product Declaration) is available